

FRAME NOMENCLATURE:

Steelcraft frames are described and marked with easy to follow product identification nomenclature. The markings identify the frames by frame series, gage (decimal and metric), fire rating, door thickness, overall depth, door opening height/width, hardware preps, component and handing.

The following is a brief guide to the nomenclature used by Steelcraft: **F 16 UL 4 5 3/4 70 SJ R ASA**

F 16 UL 4 5 3/4 70 SJ R ASA

STRIKE PREP

ASA = 4-7/8" (124mm) Strike With Lip
CYL = 2-3/4" (70 mm) Strike With Lip
RPD = Rim Exit Device Reinf.
VPD = Vertical Rod Exit Device Reinf.
SPCL = Special Strike Application

HANDING

R = Right Hand
L = Left Hand
D = Double Door
DR = Double Door, Right Hand Active
DL = Double Door, Left Hand Active

COMPONENT

SJ = Strike Jamb
HJ = Hinge Jamb
HD = Head

DOOR OPENING HEIGHT / WIDTH

Designated In Feet and Inches

68 = 6' 8" (2032 mm)
70 = 7' 0" (2134 mm)
30 = 3' 0" (914 mm)

JAMB DEPTH

5 3/4 = In 1/8" (3 mm) Increments

DOOR THICKNESS

4 = 1-3/4" (45 mm)
8 = 1-3/8" (35 mm)
CO = Cased Open Frame Profile

FIRE RATING

UL = Underwriters Laboratories, Inc.
WH = Warnock Hersey (Intertek ETL SEMKO)

GAGE OF STEEL

16 = 16 gage [0.053" (1.3 mm)]
14 = 14 gage [0.067" (1.7 mm)]
12 = 12 gage [0.093" (2.3 mm)]

FRAME TYPE

DE = Double Egress – 2 step jambs
DW = Drywall (Adjustable Base Anchor)
F = Flush 2" (51 mm) face
FE = Double Egress – 3 step jambs
FN = Flush 1" (25 mm) face
FP = Paladin
K = Drywall (Screw Base Anchor)
MU = Multiple Use 2" (51 mm) face